

DECLARATION OF PERFORMANCE

PP/NT130/CPR/4249/2018-07

Unique identification code of the product type:

TECNODREN PP/NT 130

non woven geotextile; needle punched; PP white staple fiber

Intended use of the construction product:

for roads, for tunnels, for retaining walls, for drainage systems, for resorvoirs and dams, for canals, railways foundations, vaste foundations, embankments

intended functions: separation (S), filtration (F), reinforcement (R)

Producer:

Ovattificio Alpino S.R.L., Via Ognissanti, 4, 35013 Cittadella (PD), Italy

System of assessment and verification of constancy of performance of the construction product (AVCP):

System 2+

Harmonized standard:

EN 13249:2016; EN 13250:2016; EN 13251:2016; EN 13252:2016; EN 13253:2016; EN 13254:2016; EN 13255:2016; EN 13257:2016; EN 13265:2016

The notified body:

SKZ-Testing GmbH

Notified certification body SKZ -TeConA GmbH (identification no. 1213) performed the initial ispection of the manufacturing plant and of factory production control (FPC) and the continuos surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC no. 6002,4249



Declared performance:

Essential characteristics	Performance			Harmonised technical specifications
	Test standard	Mean value	Tolerance	C POSITION OF THE PROPERTY OF
Tensile strength - longitudal (MD)	EN ISO 10319	8,4 kN/m	- 1,0 kN/m	
- transversal (CMD) Elongation		10,0 kN/m	- 1,5 kN/m	EN 13249:2016 EN 13250:2016
- longitudal (MD) - transversal (CMD)	EN ISO 10319	50% 50%	+/- 15% +/- 15%	EN 13251:2016 EN 13252:2016
Cone drop penetration Static puncture resistance	EN ISO 13433 EN ISO 12236	32mm 1,40 kN	+ 5mm - 0,3 kN	EN 13253:2016 EN 13254:2016
Characteristic opening size	EN ISO 12956	70µm	+/- 20µm	EN 13254:2016 EN 13255:2016
Water flow rate	EN ISO 11058	90 l/(m ² s)	- 20 l/(m ² s)	EN 13256:2016
Weathering resistance	EN ISO 12224	can be exposed up to 30 day		EN 13257:2016 EN 13265:2016
Oxidation resistance	EN ISO 13438	durable in natural soil with 4 <ph<9 and<br="">soil temperature <25° for a minimum of 50 years service life</ph<9>		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Cittadella, may 2020

TRENTO FERNANDO general manager