

## **DECLARATION OF PERFORMANCE**

## PP/NT150/CPR/4249/2018-07

Unique identification code of the product type:

## **TECNODREN PP/NT 150**

non woven geotextile; needle punched; PP white staple fiber

Intended use of the construction product:

for roads, for tunnels, for retaining walls, for drainage systems, for resorvoirs and dams, for canals, railways foundations, vaste foundations, embankments

intended functions: separation (S), filtration (F), reinforcement (R)

Producer:

Ovattificio Alpino S.R.L., Via Ognissanti, 4, 35013 Cittadella (PD), Italy

System of assessment and verification of constancy of performance of the construction product (AVCP):

System 2+

Harmonized standard:

EN 13249:2016; EN 13250:2016; EN 13251:2016; EN 13252:2016; EN 13253:2016; EN 13254:2016; EN 13255:2016; EN 13257:2016; EN 13265:2016

The notified body:

SKZ-Testing GmbH

Notified certification body SKZ -TeConA GmbH (identification no. 1213) performed the initial ispection of the manufacturing plant and of factory production control (FPC) and the continuos surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC no. 6002,4249



## **Declared performance:**

Essential characteristics	Performance			Harmonised technical specifications
	Test standard	Mean value	Tolerance	оростоинопо
Tensile strength				
- longitudal (MD)	EN ISO 10319	10,0 kN/m	- 1,0 kN/m	
- transversal (CMD)		11,0 kN/m	- 1,5 kN/m	EN 13249:2016
Elongation				EN 13250:2016
- longitudal (MD)	EN ISO 10319	55%	+/- 15%	EN 13251:2016
- transversal (CMD)		55%	+/- 15%	EN 13252:2016
Cone drop penetration	EN ISO 13433	30mm	+ 5mm	EN 13253:2016
Static puncture resistance	EN ISO 12236	1,70 kN	- 0,3 kN	EN 13254:2016
Characteristic opening size	EN ISO 12956	65µm	+/- 20µm	EN 13255:2016
Water flow rate	EN ISO 11058	80 l/(m <sup>2</sup> s)	- 20 l/(m <sup>2</sup> s)	EN 13256:2016
Weathering resistance	EN ISO 12224	can be exposed up to 30 day		EN 13257:2016
Oxidation resistance	EN ISO 13438	durable in natural soil with 4 <ph<9 50="" <25°="" a="" and="" for="" life<="" minimum="" of="" service="" soil="" td="" temperature="" years=""><td>EN 13265:2016</td></ph<9>		EN 13265:2016

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer by:	
Cittadella, may 2020	
	TRENTO FERNANDO