

DECLARATION OF PERFORMANCE

DoP HI - 231/23-01 according to REGULATION (EU) No 305/2011 laying down harmonised conditions for the marketing of construction products:

Unique identification code of the product type:

SKYFLEX TOP PV 5 DESIGN

bitumen sheet with a polyester fleece carrier and with elastomer bitumen; $8m \times 1m \times 6.5 \text{kg/m}^2$ surface protection: sand / polymeric sheeting

Intended use of the construction product:

waterproofing membrane used for multilayer systems without permanent heavy surface protection – top layer (EN 13707)

Producer:

Fragmat S d.o.o. Šid, Branka Erića br.7, 22240 Šid

System of assessment and verification of constancy of performance of the construction product (AVCP):

System 2+

Harmonized standard:

EN 13707:2004+A2:2009 a EN 13969:2004 a EN 13969:2004/A1

The notified body:

1404 - Zavod za gradbeništvo Slovenije, Dimičeva 12, 1000 Ljubljana



Declared performance:

Essential requirement:	Performance			Harmonized technical specification
	EN Method	Unit	Declaration	
Watertightness	1928	kPa	≥ 100	
Flexibility at low temperature	1109	°C	≤ -15	
Shear resistance of joints				
- longitudal	12317-1	N/50mm	NPD	
- transversal			NPD	
Resistance to tearing				
- longitudal	12310-01	N	NPD	
- transversal			NPD	
Reaction to fire	13501-1	class	E	
External fire performance	13501-5	class	F _{ROOF}	
Resistance to static loading	12730/A	kg	NPD	
Resistance to impact	12691/A	mm	NPD	
Tensile strength				EN 13707:2004+A2:2009
- longitudal	12311-1	N/50mm	≥ 700	EN 13707:2004+A2:2009
- transversal			≥ 500	
Elongation				
- longitudal	12311-1	%	≥ 35	
- transversal			≥ 35	
Flexibility at low temperature against artificial ageing by long term	1296/1109	°C	≤ -15	
exposure to elevated temperature (12 weeks at 70°C)	1230/1103	Ŭ	=-10	
Flow resistance at elevated temperature against ageing by long term exposure to elevated temperature (12 weeks at 70°C)	1296/1110	°C	≥ 90	
Resistance to root penetration	13948	-	NPD	†
Chemical resistance	1847/13707 Annex C	-	pass	1
Content of hazardous substances	Annex ZA	1	does not contain]

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Šid, 20.03.2023

